

 **hi-view**[®]

IP CAMERA

P2P / WIFI / AUDIO

HP-ROBOT13



Robot Camera



Model	HP-ROBOT13
Sensor	1/3" SC1035+HI3518E
Scan system	Progressive Scan
Pixels	1280x960P (1.3MP).
Min. Illumination	0.5 Lux, 0 Lux with IR
Exposure Mode	Auto,1/50, 1/120,1/250,1/500,1/1000,1/2000,1/4000,1/10000
Day / Night	ICR (IR CUT), (Auto,B/W,External)
Auto Iris	Electric Iris
Focal Length	Fixed HD Lens 3.6mm./F1.2
IR Type	IR LED 11Pcs, Φ 5mm
IR Distance	10M.
IR Intensity	SMART IR
Compression Format	Standard H.264 High Profile
Compression Format	G.711, ADPCM/32kbps
Signal System	PAL/NTSC
Multi Stream	Dual Stream
Bitrate Control	VBR/CBR
Image Resolution	960P,720P,D1,CIF,QCIF
Encode Main Stream	*960P@25fps, 1024-5120Kb/s, 720P@25fps, 768-3072Kb/s, D1@25fps, 384-1920Kb/s.*
Encode Main Stream	*D1@25fps, 384-1920Kb/s, CIF@25fps, 48-768Kb/s, QCIF@25fps, 48-384Kb/s.*
Cloud P2P	Support (hiviewonline.com)
Apps	Xmeye
Privacy Masking	Support adjustable
Motion Detection	Support adjustable
Wide Dynamic Range (WDR)	Support (Level 1-100)
Digital Defog	Support (Level 1-100)
White Balance	Support
Gain Control (AGC)	Support adjustable
Backlight Compensation	Off / BLC /AWB/ATW
Digital Noise Reduction (DNR)	Support
Mirror	Support
Image Flip	Support
Auto Flicker	Support
Audio Function	2-Way-Audio
IP Filter	Support
Wifi Antenna	Support
DDNS	Support Hiview DDNS, CN99, DynDNS, Oray, NO-IP, MYQ-SEE
Alarm server	Support
Mobile report	Support
Digital zoom	Support browsers live view (IE, VMS)
User Interface	IE 11, VMS, NVR
Application Program	Support Onvif
Etc.	*Online upgrade, Reboot, Import&Export File config, Default, Auto maintain, Account management Support camera param., GUI display adjust, LOG.*
Intelligent	Motion Alarm, Storage device not exist, Storage space lack alarm, Storage failure, IP conflict
Alarm Triggers	Send Email (1xReceiver) , Mobile reported , FTP, White log
Network Protocol	TCP/IP, UDP/IP, HTTP, SMTP, FTP, DHCP, DDNS, UPNP, NTP, ARSP,WI-FI, RTSP, DAS, Cloud.

Robot Camera



Model

HP-ROBOT13

Pan rotation range	Horizontal 355C
Tilt rotation range	Vertical 90C
Pan speed	1-8Step
Tilt speed	1-8Step
Ethernet	1x10/100Mbps, RJ45 interface
Wifi Antenna	"1xSupport wireless standards IEEE 802.11b/g/n data rate 802.11b: 11Mbps (Max.) 802.11g: 54Mbps(Max.) data rate 802.11n: 150Mbps (Max.) "
Audio In / Out	Build in microphone, Speaker
Memory Slot	SD card 128GB. (kingston class 10)
Reset Bottom	Support
Protection Level	N/A
Operating Temperature.	-20C~+55C (32F ~ 131F)
Operating Humidity	10% ~ 80% non-condensing
Storage Temperature	-20C-60C(14F-140F)
Storage Humidity	0% ~ 90% non-condensing
Power	DC5V+-10% /1A.(DC Jack Powerinput)
Power Consumption	N/A
Case	Plastic
Weight	308g. (Without Bracket)
Dimensions	200x179x120 mm.
Certificate	CE,FCC
	"Support LOG (Export)
	Support SD card 128GB. (kingston class 10)
	Support Network upgrade device
	Support Reboot
	Support Import/Export file config.
	Support Camera parameter adjustable
	Support Privacy mask
	Support IP Filter
	Support Hiview DDNS, CN99, Dyndns,Oray, NO-IP
	Support SMTP Email notification
	Support NTP (Network Time Protocol)
	Support PPPoE
	Support ARSP
	Support UPNP
	Support FTP
	Support Wi-Fi
	Support RTSP
	Support Cloud (P2P) , Xmeye, hiviewonline.com
	Support Mobile reported
	Support Motion detection
	Support video loss detection
	Support Abnormal
Support Record mode manual/Config,Snapshot	
Support IE Playback 1ch.	
Support Download backup (H.264/AVI)	